TRUBUILD
MOULD RELEASE AGENT

Trubuild MRA (Mould Release Agent) is a ready to use mix which is used as a release agent of moulds or shuttering. It can be used on moulds and framework made of various substrates like wood, steel, plywood etc.

APPLICATIONS

It can be used on moulds and framework made of various substrates like wood, steel, plywood etc.

HOW TO USE

- The rusted moulds and framework should be cleaned properly before use, with the help of emery paper or wire brush.
- It should be followed by cleaning through wet cotton cloth to remove dust & dirt.
- Now apply one coat on the mould or framework by spray or with the help of brush or roller.
- Allow it to dry completely before casting of concrete.
- For better finish of concrete, two coats are recommended on wood or plywood shuttering.
- Excess usage of Trubuild MRA should be avoided as can give imperfect concrete finish.

Thakorji
DISTRIBUTORS
+91 95375 65835

TRUBUILD WATER PROOFING

TECHNICAL INFORMATION

PROPERTIES	RESULTS
Physical State	Low Viscous
Appearance	Transparent
Color	Yellow
Specific Gravity	0.82-0.83

COVERAGE

8-12 m^2/ltr (Timber)

12-15 m^2/ltr (Metal & Plastic)

STORAGE

Product should be stored in a dry place in its original, properly closed container at temperature between 2°-40° C. Partially emptied container should be closed immediately.

SHELF LIFE

1.5 years.

HANDLING PRECAUTIONS

Mandatory and recommended industrial hygiene procedures should be followed whenever products are being handled and processed. For additional information please refer the corresponding product data sheets.

PACKING

1 ltr, 5 ltr & 20 ltr