

### Product Description :

**MYMIX - FTA** (Floor Tile Adhesive) is a thin set cementitious dry mix mortar for installing ceramic, vitrified tiles and natural stones for interior floor & walls applications. **MYMIX - FTA** is polymer modified tile adhesive which make it ideal for fixing tiles, natural stones and granite to most building substrates

### Application :

- Specially for internal floors and walls
- Small and medium size tiles fixing

**FOR BETTER APPLICATION  
USE A NOTCH TROWEL OF  
APPROPRIATE NOTCH SIZE**

### Advantages :

- Easy to apply, single component adhesive
- Extended open time
- Superior adhesion properties with adhesion to various substrates
- Dual purpose for floor and wall with good adhesion workability
- Suitable for solid subfloors

### Suitable Substrates :

- Concrete
- Tile-on-tile application
- Cement mortar beds
- Thin-set cementitious screeds
- Cement plaster

### How to apply :

- Add 25 kg of "**MYMIX - FTA**" (Floor Tile Adhesive) to approx. 6.5 to 7.5 litres of cool and clean tap water and stir properly for 5 minutes by hand or an electric stirrer to get a smooth and homogeneous mixture
- After stirring; wait for 10 minutes, stir once again and apply the adhesive on the sub-floor with the recommended adhesive notch trowel

- Press the tiles within 15 to 20 minutes with a shuffling movement into the adhesive. Check properly to ensure that the back of the tile is in full contact with the adhesive
- Remove excess adhesive immediately from the joints
- The proper preparation of the surface will make the fixing easier and quicker ensuring a better finish
- New concrete is recommended to be 1 month old forevery 25 mm thickness and completely dried before tiling
- Under normal circumstances, i.e. a temperature of 20°C and a relative humidity of 65%, the joints may be filled after minimum 24 hours

### Technical Details : (As per IS 15477 & ANSI 118.1)

Sr. No.	Testing Parameter	Specification
1	FTA - Mixing Ratio	6.5 to 7.5 litre water for 25 kg material approx 25-30% by weight
2	Product Colour	Grey and White
3	Workability	Easy mixing and self curing
4	Application	Easy spreading
5	Open time @ 23-27°C	30 - 45 minutes
6	Pot Life	3 -4 hours
7	Setting time	24 hours
8	Trafficable Time	24 hours
9	Shear Adhesion :	
A	Dry condition after 24 hrs	3.8 KN
B	Dry condition after 14 days	14.50 KN
C	Heat ageing condition	11.50 KN
D	Wet condition	10.80 KN
10	Tensile Adhesion	
A	Dry condition	1650 N
B	Wet condition	1425 N

### Coverage :

- At 3 mm bed thickness 65-75 sq. ft./ per 25 kg bag.

### Storage :

- Store in a cool & dry place. Protect from direct sunlight.

### Colour :

- Grey and White

### Packing Detail :

- Available in 25 kg bag
- Available in 40 kg bag Project pack on demand

### Shelf Life :

- 12 months from the date of manufacturing in unopen condition



**Inakorji**  
D I S T R I B U T O R S  
+91 95375 65835